

- SAFETY FIRST!**
- Please read these instructions carefully.
  - Always use caution and wear protective gear such as gloves and safety glasses during operation.
  - Keep away from children.
  - Use this tool at your own risk and with caution. The seller is not liable for misuse or accidents caused by improper operation.

**WOODRANGER**  
**MINI POWER CHAINSAW**  
 EASY-TO-FOLLOW GUIDE



4 INCH BATTERY POWERED CHAINSAW

**Important Reminders**  
 Regularly apply lubricant to the chain during cutting.  
 SUPPORT@WOODRANGERTOOLS.COM  
 WOODRANGERTOOLS.COM

Scan this QR code with your smart phone camera for video setup, tutorials, and support.



**WHAT'S INCLUDED**

- ▶ WoodRanger Mini Power Chainsaw
- ▶ 24V Lithium-Ion Battery
- ▶ 4" Chain
- ▶ Guide Bar
- ▶ Screwdriver
- ▶ Wrench
- ▶ Charging Cable and Plug

**CHARGING THE BATTERY**

- ▶ Connect the battery to the charger.

**Red Light:** Charging in progress.

**Green Light:** Fully charged.

Charging time is roughly 2 hours.

**INSTALLING THE CHAIN**

- ▶ **Open the Side Cover**  
 Use the provided wrench to loosen the nut and remove the side cover.

**Mount the Chain**  
 Fit the chain onto the metal guide bar, ensuring the drive links slot securely into the guide groove.

**CHECK YOUR ORIENTATION**

The chain only works in one direction. To cut safely and properly, you must identify the two parts of each link:

■ **The Small Tooth (Depth Guide):**  
 This is the rounded "bump." It must be in the front, leading the way into the wood.

■ **The Large Tooth (Cutter):**  
 This is the tooth with the sharp edge. It must follow immediately behind the small tooth.



- ▶ **Verify Cutting Direction**  
 The sharp edge of the Large Tooth must point toward the material you are cutting (away from the motor) on the top of the bar.

For guidance, refer to our instructional video:  
<https://woodrangertools.com/support/articles/chainsaw-instructions/>

**ATTACHING THE GUIDE BAR**

- ▶ Place the guide bar onto the chainsaw.  
 Ensure the screw base starts at the bottom.  
 Align the screw base with the hole in the metal guard.  
 Wrap the chain around the motor's wheel.

Consult our video for detailed instructions.

**TIGHTENING THE CHAIN**

- ▶ Use the provided screwdriver to turn the screw clockwise. Tighten until snug, but avoid over-tightening.

There should be 3 chain teeth visible when pulling the chain downwards.

**REINSTALLING THE SIDE COVER**

- ▶ Use the same wrench to put back the side cover you previously removed.

**INSERTING THE BATTERY**

- ▶ Install the battery when it shows a green light, indicating a full charge.

